

# imagePROGRAF PRO-6000S

Reliable production of large format advertisements, graphics and posters.

The imagePROGRAF PRO-6000S is the best solution for very large format (up to 60") printing productivity, delivering outstanding production quality at high speed, and offering exceptional reliability.



- Outstanding LUCIA PRO 8-colour print quality at impressive speeds, with up to 60" large format production output.
- A new 1.28" wide print head enables faster printing while maintaining high quality.
- Dual roll unit supports continuous paper feeding or automatic take-up of printed output.
- Visually attractive and distinctive, black body hardware design.
- Ergonomic design with a flat top surface for print checking and a 3.5" colour LCD touch screen operation panel.
- Introducing the optimum space-saving compact body for production environments.
- Fast and easy printing of PDF and JPEG file formats directly from USB memory stick.
- Wi-Fi functionality for easy connection and quick setup to wireless networks.
- High-capacity "hot swap" ink tanks for uninterrupted printing.
- Guaranteed colour consistency between jobs and different production sites.

**Canon**

## TECHNOLOGY

<b>Printer Type</b>	8 Colour 60"/1524 mm
<b>Print Technology</b>	Canon Bubblejet on Demand 8 colours integrated type (12 chips per print head x 1 print head)
<b>Number of Nozzles</b>	18,432 nozzles (1536 nozzles x 12 colour)* *The four key colours (C, M, Y, MBk) are arranged symmetrically on the print head
<b>Print Resolution</b>	2400 dpix/1200dpi
<b>Nozzle Pitch</b>	600 dpi x 2 includes Non-firing nozzle detection and compensation system
<b>Line Accuracy</b>	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.
<b>Ink Droplet Size</b>	minimum 4 pl per colour
<b>Ink Capacity</b>	Sales ink: 160ml/330ml/700ml Bundled Starter ink: 330ml (C, M, Y, MBk), 190ml (PC, PM, Bk, GY)
<b>Ink Type</b>	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey
<b>OS Compatibility</b>	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11 SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)
<b>Printer Languages</b>	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b
<b>Standard Interfaces</b>	

## MEMORY

<b>Standard memory</b>	3 GB
<b>Hard Drive</b>	320 GB

## PRINT TIME FOR A0 PAGE SIZE

	<b>Print Mode</b>	<b>Print Time</b>
<b>Plain Paper</b>	Fast	0:55 min
	Standard	2:51 min
<b>Coated Paper</b>	Fast	1:35 min
	Standard	2:51 min
<b>Glossy Photo Paper</b>	Fast	2:58 min
	Standard	4:46 min

## MEDIA HANDLING

<b>Media Feed and Output</b>	Roll Paper: Two Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)
<b>Media Width</b>	Roll paper: 203.2 mm- 1524 mm Cut sheet: 203.2 mm- 1524 mm
<b>Media Thickness</b>	Roll/Cut: 0.07 mm- 0.8 mm
<b>Minimum Printable Length</b>	203.2mm
<b>Maximum Printable Length</b>	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
<b>Maximum Media Roll Diameter</b>	170 mm
<b>Media Core Size</b>	Internal diameter of roll core: 2"/3"
<b>Margins Recommended area</b>	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

## Margins Printable area

## Media Feed Capacity

## Media Take-up roll unit

## Borderless Printing Width (Roll Only)

## Maximum number of delivered prints

## DIMENSIONS AND WEIGHT

### Physical Dimensions WxDxH (mm) and Weight (Kg)

### Packaged Dimensions WxDxH (mm) and Weight (Kg)

## POWER AND OPERATING REQUIREMENTS

### Power Supply

### Power Consumption

### Operating Environment

### Acoustic Noise (Power/Pressure)

### Regulations

### Environment Certificates

## WHAT'S INCLUDED

### What's in the Box?

### Software Included

## OPTIONS

### Optional items

## CONSUMABLES

### User Replaceable Items

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm Roll Paper: Two roll automatic switching possible Cut Sheet: 1 sheet
Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll
515 mm(JIS B2), 728 mm(JIS B1), 1030 mm(JIS B0), 594 mm(ISO A1), 841 mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60", 257 mm(JIS B4)*, 297 mm(ISO A3)*, 329 mm(ISO A3+)*, 420 mm(ISO A2)*, 8", 16", 30", 300 mm*
*Some environmental conditions may not produce the desired result.
Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1999 mm x 984 mm x 1168 mm (Basket Opened) 1999 mm x 766 mm x 1168 mm (Basket Closed) Weight approx x 137 kg (excluding ink and print heads)
Printer: (Main unit and stand with pallet): 2227 mm x 915 mm x 1022 mm, Weight approx: 211 kg Roll unit: 2133 mm x 562 mm x 461 mm, Weight approx: 40 kg

AC 100-240V (50-60Hz) Operation: 113 W or less Standby: 1.8 W or less Power off: 0.5 W or less
Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation) Operation: 49 dB (A) (Glossy paper, Print priority: Standard) Standby: 35 dB (A) or less Operation: 6.7 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)
Europe: CE mark, Germany: TUV mark, Russia: EAC, Other countries: CB certification International Energy Star Program (WW), RoHS

Printer, 1 x print head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard Environment Leaflet, User Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite  
Other software available as Download from Web.

Roll Unit: RU-61 \*This is a mandatory item  
2/3" Roll Holder: RH2-65

Ink Tank: PFI-1100 (160 ml), PFI-1300 (330 ml), PFI-1700 (700 ml)  
Print Head: PF-10  
Cutter Blade: CT-07  
Maintenance Cartridge: MC-30

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Crystal-fidelity



**BUSINESS EQUIPMENT LTD.**  
Supplies Sales & Service

13, 9151- 44 ST. S.E. Tel: (403)251.5304  
Calgary, AB. T2C 2P7 Fax: (403)251.4085  
Website: www.randsbus.com Email: rands@telus.net

